



**CERTIFICATE OF COMPLIANCE**

Name:

Date:

Attn:

Project:

**PRODUCTS & MATERIAL**

Metalfit manufactures Ductile Iron and Gray Iron AWWA C110 Flanged Fittings for both Waterworks and Industrial applications and conforms fully to all required industry standards. Metalfit also produces C 153 Mechanical Joint Fittings in sizes ranging from 4" through 48". The production facility is located in Monterrey, N.L. Mexico. We are a North American Free Trade Agreement compliant producer.

We hereby certify that all materials furnished by Metalfit are manufactured and tested in accordance with the following standards, and meet or exceed the requirements and recommendations therein.

- Cast Iron Flanged Fittings.....ANSI B16.1, Class 250
- Ductile Iron Flanged Fittings.....ANSI / AWWA C110 / A21.10 ANSI B16.1, Class 125
- Cast Iron Flanged Fittings.....ANSI / AWWA C110 / A21.10 ANSI B16.1, Class 125
- Ductile Iron Flanged Fittings.....ASTM A 536 for Mechanical Properties
  - Minimum Tensile Strength 70,000 psi
  - Minimum Yield Strength 50,000 psi
  - Minimum Elongation 5%
- Cast Iron Flanged Fittings.....ASTM A 48, minimum tensile 31,000 psi
- Cement Mortar Lining.....ANSI / AWWA C104 / A21.4
- Protecto 401 Lining.....In accordance with the "Licensed Applicator Agreement"
- Standard Coatings and Linings.....ANSI / NSF 61
- Compact Mechanical Joint Fittings.....ANSI / AWWA C153 / A21.53
- Cast Iron Water Working Pressure.....2" through 12" - 250 psi
  - 14" through 42" - 150 psi
- Ductile Iron Water Working Pressure.....2" through 42" - 250 psi
- Ductile Iron Water Working Pressure.....ANSI / AWWA C111 / A21 / 11, states that 2" through 24" may be rated to 350 psi with the use of "special" gaskets

Mark Meyer  
Vice President

5583 Snowflake Way  
Parker, CO 80134

303-840-2183 Main  
303-840-2193 Fax  
303-941-0180 Cell

metalfit1@aol.com